

TECHNICAL SPECIFICATIONS OIL TRAWL



NO-T-600-S	
OPERATIONAL DATA	
Wave height maximum	2,0 meter
Wave height significant	1,0 meter
Wind force normal	14 m/s
Wind force maximum	18 m/s
Towing speed during oil recovery	<2 m/s (< 4 knot)
Towing force minimum	4,0 kN
Towing force maximum	16,4 kN
PHYSICAL DATA	
Diameter freeboard	600 mm
Length guiding booms (each side)	24 m
Inlet	25 m
Skirt depth	150-300 mm
Breaking strength tension member top	23,5 kN
Ballast / tension member bottom	13x82 mm Galvanized chain
*Weight ballast	2,95 kg/m
*Breaking strength Tension member bottom	159 kN
Storage volume	4,7 m ³
Buoyancy / weight ratio	34/1
Weight boom	8,5 kg/m
MATERIALS	
*Freeboard, skirt and splitter	900 g/m ² PVC-coated fabric
*Bag	1250 g/m ² PVC/TPU-coated fabric
Tension member top	50 mm PVC-coated polyester webbing
Ballast / tension member bottom	Galvanized steel
Color	Orange

All values marked (*) can vary to some extent

For more information please contact
Robin Mattson on 24 hour phone +61 (0) 408 783 585
www.amsnor.com.au or rmattson@amsnor.com.au