

## TECHNICAL SPECIFICATIONS OIL TRAWL



NO-T-1000-S	
OPERATIONAL DATA	
Wave height maximum	5,0 meter
Wave height significant	2,5 meter
Wind force normal	18 m/s
Wind force maximum	22 m/s
Towing speed during oil recovery	<2 m/s ( < 4 knot)
Towing force minimum	20 kN
Towing force maximum	82 kN
PHYSICAL DATA	
Diameter freeboard	1000 mm
Length (each side)	50 m
Inlet	50 m
Skirt depth	500mm
Ballast / tension member bottom	16x100 mm Galvanized chain
*Weight ballast	4,45 kg/m
*Breaking strength Tension member bottom	222 kN
Storage volume	13 m <sup>3</sup>
Buoyancy / weight ratio	39/1
Weight boom	22 kg/m
MATERIALS	
*Freeboard, skirt and splitter	900 g/m <sup>2</sup> PVC-coated fabric
*Bag	1250 g/m <sup>2</sup> PVC/TPU-coated fabric
Ballast / tension member bottom	Galvanized steel
Color	Orange

All values marked (\*) can vary to some extent

**For more complementary information, please contact NorLense**  
[www.norlense.no](http://www.norlense.no) or [firmapost@norlense.no](mailto:firmapost@norlense.no)

QUALITY APPROVED		
Edition	Valid from	Revision date
5	01.10.13	11.09.14
Signature	Jannicke Johansen	